

Renhotec Electronics



- We make connection easier

www.renhotecpro.com

sale@renhotec.com



M8 Sensor Connectors & Cables



M8 Panel Mount Receptacles

01



M8 Field Wireable Connectors

02



M8 Molding Cables

03

M8 Female Panel Mount



M8 Female PCB Front Mounting Connector

Gender: Female
Number of Contacts: 3Pin /4 Pin /5Pin /6Pin /8Pin
Coding: A-Code
Termination: PCB /Soldering




Electrical & Mechanical data

Connection type: Panel mount, Front fastened
Orientation: Straight
Insert/ Housing: TPU
Rated current: 3 A
Connector contacts: Brass with gold plated
Rated voltage: 30V
Ambient temperature: -40°C ~ + 85°C
Coupling nut/screw: Brass with nickel plated screw
IP rating: IP67



M8 Male Panel Mount



M8 Male Panel Receptacle Solder Contacts Front Mounting With Wires

Gender: Male
Number of Contacts: 3Pin /4 Pin /5Pin /6Pin /8Pin
Coding: A-Code
Termination: Soldering
Cable length:base on customer request



Electrical & Mechanical data

Connection type: Panel mount, Front fastened
Orientation: Straight
Cable jacket material: PVC/PUR
Wire gauge: 26AWG/0.14mm² (By custom)
Insert/ Housing: TPU
Rated current: 3 A
Connector contacts: Brass with gold plated
Rated voltage: 30V
Ambient temperature: -40°C ~ + 85°C
Coupling nut/screw: Brass with nickel plated screw
IP rating: IP67



M8 Male Field Installable Connector



M8 Male Straight Assembly Cable Plug

Gender: Male
Number of Contacts: 3Pin /4 Pin
Coding: A-Code
Termination: Screw-Joint



Electrical & Mechanical data

Connection type: Field wireable
Orientation: Straight
Wire gauge: 24AWG/0.25mm² (By custom)
Wire Termination: Screw-joint
Insert/ Housing: TPU
Rated current: 3 A
Connector contacts: Brass with gold plated
Rated voltage: 30V
Ambient temperature: -40°C ~ + 85°C
Coupling nut/screw: Brass with nickel plated screw
IP rating: IP67

M8 Female Field Installable Connector



M8 Female Straight Assembly Cable Plug

Gender: Female
Number of Contacts: 3Pin /4 Pin
Coding: A-Code
Termination: Screw-Joint



Electrical & Mechanical data

Connection type: Field wireable
Orientation: Straight
Wire gauge: 24AWG/0.25mm² (By custom)
Wire Termination: Screw-joint
Insert/ Housing: TPU
Rated current: 3 A
Connector contacts: Brass with gold plated
Rated voltage: 30V
Ambient temperature: -40°C ~ + 85°C
Coupling nut/screw: Brass with nickel plated screw
IP rating: IP67

M8 Molding Cable



M8 Male & Female Molding Cable

Gender: Male/Female
Number of Contacts: 3Pin /4 Pin /5Pin/6Pin/8Pin
Coding: A-Code
Termination: Soldering
Cable length: base on customer request



Electrical & Mechanical data

Cable jacket material: PUR/PVC
Connection type: Single ended/Double Ended
Orientation: Straight/Right Angle
Wire gauge: 24AWG/0.25mm²/26AWG/0.14mm² (By custom)
Insert/ Housing: TPU
Connector contacts: Brass with gold plated
Ambient temperature: -40°C ~ + 85°C
Coupling nut/screw: Brass with nickel plated screw
Shielding: Available
IP rating: IP67



M Series Connectors & Cables



Renhotec Group's M5/M8/M12 Connector System includes a broad range of straight, angled, LED and multi-position field installable and board connectors that are easily intermateable .

Renhotec offers a complete line of M5/M8/M12 connector solutions with variety of types, such as Panel Mount Receptacle, Field Wireable Assembly Cable Plug and Molding Cable .

THANK YOU

Please feel free to contact us to get free samples for testing .

Welcome to view our web:

[-www.renhotecpro.com](http://www.renhotecpro.com)

[-www.elecbee.com](http://www.elecbee.com)

Welcome to contact us:

[-sale@renhotec.com](mailto:sale@renhotec.com)

